

TR-1200S



A-TECHEL THERMO Co., Ltd.
 108, Anseongmatchum-daero, Seoun-Myeon, Anseong-si, Gyeonggi-do, Republic of KOREA
 tel: +82-31-667-1230, fax: +82-31-677-9981
 website: <https://www.atechelthermo.com>, e-mail: sales@atechelthermo.com

**High performance refrigeration unit for middle size truck have about 45 ~ 50m³ storage volume.
 Box Length In 10 Meters**

Description

One of A-TECHEL THERMO's self-powered engine driven units in TR series is refrigerator system with professionally designed and manufactured for fresh and frozen applications on middle size truck.

Evaporator

- PLATE FIN TYPE
- 3 Fans - diam. 280 mm
- Air Volume : 3650m³/h
- Designed Air speed : 9.7 m/s

Electric standby

- 9Kw, High Performance AC Motor
- 220V / 380V / 415V, 3-Phase, 50 / 60 Hz

Compressor


- Bltzer-4PFRY- Germany
- Displacement : 558cc

Engine

- YANMAR / EPA Final Tier3 / 3TNV-76 / japan
- Oil charge : 8.7L / KUBOTA / D - 1105 /1123CC Oil3.8 L

Refrigerant

- HFC R-404a
- Chlorine - Zero
- Refrigerant charge : 4.2 Kg +/- 100g



- Defrost Control
 - Manual Defrost : controlled by pushing button manually
 - Auto Defrost : controlled by pressure difference
 - Timer Defrost : controlled by pre set-up cycling time of timer
- System Protection
 - Engine cut off at low oil pressure
 - Engine cut off at high coolant temperature
 - Compressor cut off at high or low pressure of system
 - Compressor cut off at high temperature of comp. body
- Temperature Control
 - Engine stop/start based on fixed temperature / Manual control also possible



Refrigeration Capacity

Ambient temperature at 30°C / 86°F

	Engine Driven		Electric Motor Driven (option)		Weight
	0 °C	-20 °C	0 °C	-20 °C	
R404A					560 Kg
Watts	11000	7300	8000	5700	
Kcal/h	9464	6281	6883	4904	
BTU/h	37553	24923	27297	19459	

※ Specifications can be changed without notice in advance.